

Battery Testers

Battery Internal Resistance Tester

Model: ES8020



General Information

| Model | ES8020 |
|----------------------|---|
| Power supply | DC 3.7V lithium battery |
| Product size | 190mmx121mmx51mm |
| Product weight | 480g |
| Standard accessories | USB cable, charger, software CD, manual, test leads, tool box |

Specifications

| opcomoditons | | | |
|--|---------------------|------------|--|
| Resistance measurement ($0.000 m\Omega \sim 3.100 \Omega$) | | | |
| Range | Resolution | Accuracy | |
| 3mΩ | 1υΩ | ±1 % ±20 | |
| 30mΩ | 10uΩ | ±0.5 % ±15 | |
| 300mΩ | 100uΩ | ±0.5 % ±15 | |
| 3Ω | 1 m Ω | ±0.5 % ±15 | |
| Voltage measurement (0.000V~±71.00V) | | | |
| 7V | 1mV | ±0.2 % ±10 | |
| 70V | 10mv | ±0.2 % ±10 | |
| Temperature measurement (-10.0°C~60.0°C) | | | |
| -10.0°C~60.0°C | 0.1℃ | ±1.0℃ | |
| Response time | 200ms | | |
| Measure time | 2 seconds | | |
| Power consumption | 300mA Min/500mA Max | | |

Features

| reatures | |
|-----------------------------|--|
| Model | ES8020 |
| Auto off | \checkmark |
| Data hold | \checkmark |
| Data store | \checkmark |
| Battery voltage display | \checkmark |
| Bluetooth function | connect to APP |
| 3 in 1 measurement function | Battery internal resistance, Battery voltage, Temperature |
| Display (LCD) | 70.1mm×52.6mm, 3.5 inches ,320*240 resolution ,16-bit true color |
| Judgment function | Pre-set PASS, WARNING, FAIL judgment |
| Interface | USB, the stored data can be uploaded to the computer, saved, and printed |
| Working condition | -10°C ~ 40°C, <80%RH |
| Storage condition | -20°C ~ 60°C, <70%RH |