

Digital Clamp Earth Resistance Testers  
Model: 6410+ 6412A



**Features**

Model	6410+	6412A
Alarm beeping	√	√
Clock display	√	√
Date hold	√	√
Auto power off	√	√
Double insulation	√	√
Range	Auto range	Auto range
Display resistance + current at the same time	---	√
<b>Bluetooth connect to APP, for remote control</b>	---	√
<b>USB interface for data transfer</b>	---	√
Data storage	500 groups	
Clamp size	55mmx32mm	
Display	4 digits VA screen ,46x36mm	
Working Condition	(-10 ~ 40)°C; <80%Rh	

**Specifications**

Function	Range	6410+	6412A
Resistance range	0.010Ω~0.199Ω	±1.0%+0.02	±1.0%+0.02
	0.20Ω~1.99Ω	±1.0%+0.05	±1.0%+0.05
	2.0Ω~49.9Ω	±1%+0.5	±1%+0.5
	50.0Ω~99.5Ω	±1.5%+1	±1.5%+1
	100Ω~199Ω	±2.0%+2	±2.0%+2
	200Ω~395Ω	±5.0%+5	±5.0%+5
	400Ω~590Ω	±10.0%+10	±10.0%+10
	600Ω~880Ω	±20.0%+20	±20.0%+20
AC current range	900Ω~1200Ω	±25.0%+30	±25.0%+30
	1.00mA-9.99mA		±2.5%+1
	10.0mA-99.9mA		±2.5%+5
	100mA-999mA	---	±2.5%+10
	1.00A-9.99A		±2.5%+0.2
	10.0A-20.0A		±2.5%+0.5
Single measurement time		1s	1s
Current measure frequency		---	50/60Hz Auto

**General Information**

Model	6410+	6412A
Power supply	1.5V AA*4, or DC6 V adapter	
Product color	Black + orange	
Product size	293mm(L) X 90mm(W) X 66mm(H)	
Product weight	1320g	
Standard accessories	verification resistor, batteries, manual, tool case, USB cable (only for 6412A)	