

Stage Lighting Equipment Supplier Expert

USER'S MANUAL

Waterproof LED Par 18x18W RGBWA+UV Lighting



Maintenance

- 1. Please keep the light in dryness and avoiding use in wet place.
- 2. Using intermittenlly can be extended the life.
- 3.Attention to clean the fan and lens usually in order to get the ventilating effects and lighting effects better.
- 4. Please do not wipe the crust using organic menstruum for avoid to damaged the product.

Statement

The product has well capability and intact packing when leave factory, All of the user should comply with above warning item and manual , any misuse cause of the damages are not included in our guarantee, and also can't be responsible for any malfunction & problem owing to ignore the manual. Please forgive that we will not be notice for technical change

Attention Item

- 1. For guarantee the life of product, please do not put it on the wet place and not use it the place over 40 degree.
- 2.Please don't lay the product on the un-fixable or shakable place.
- 3. Ask for the professional to maintain the product in order to avoid the danger of get an electric shock.

- 4.Power supply should not be changed over +&-10% while the light is using, it will be decreased the life of lamp if the power is too high, but it will be influenced the luminosity if the power is too low.
- 5. After power off, if it is need used again, please cool down over 20 minuter.
- 6.Please look round the manual for ensure the product can be used normally.

DMX Channel Summary-6 Channels Mode

Channel	Value	Function				
CH1	0-255	Red Dimmer				
CH2	CH2 0-255 Green Dimmer					
CH3	0-255	Blue Dimmer				
CH4	0-255	White Dimmer				
CH5	0-255	Amber Dimmer				
CH6	0-255	Ultraviolet Dimmer				

DMX Channel Summary-10 Channels Mode

DIVIX Charmer Summary 10 Charmers Wood							
Channel	Value	Function					
CH1	0-255	Total Dimmer					
CH2	0-255	Red Dimmer					
CH3	0-255	Green Dimmer					
CH4	0-255	Blue Dimmer					
CH5	0-255	White Dimmer					
CH6	0-255	Amber Dimmer					
CH7	0-255	Ultraviolet Dimmer					
CH8	0-255	Strobe					
СН9	51-100	Auto Mode 1					
	101-150	Auto Mode 2					
	151-250	Auto Mode 3					
	250-255	Sound Mode					
CH10	0-255	Function Speed Adjustment – CH9					

No	Display	Function					
r00 I	0-512	10 Channel DMX Address					
400 I	0-512	6Channel DMX Address					
r00 I	0-255	Red Dimmer					
600 (0-255	Green Dimmer					
P00 I	0-255	Blue Dimmer					
U00 I	0-255	White Dimmer					
A00 I	0-255	Amber Dimmer					
P00 I	0-255	Ultraviolet Dimmer					
Fh0 I	0-99	Flash					
cLO I	0-8	Color Choice					
dE0 1	0-99	Color Gradient					
cP0 1	0-99	Color Pulse					
5Uo9	1-9	Sound Control					

Display Control Instruction

Welcome to use our light. The light uses energy-saving LED, long Product life, shockproof, dustproof, DMX receiver and self-running feature, which can produce a variety of vivid lighting effects, easy to operate, suitable for all types of entertainment decoration, architectural lighting industry.

			E	
A:Function				
B:Up				
C:Down				
D:Enter				
E:LED Display				
	Α	В	С	D

Instructions:Press the function key A cycled out the eight different function effects, digital tube first two digits on behalf of which the current function (see menu). The last two digits represent the functions in which the address code or speed parameters. Press the B or C key to modify the parameter values. Press the D key to confirm.

Product Introduction

- * Power Supply:AC90--275V,50--60HZ
- * Power consumption:324W
- * Fixing lamp:LED 18×18W RGBWA+UV
- * DMX-Control-channels:6/10 DMX Channels
- * Shuttle:Flash rate:0--10HZ
- * Dimmer:0-100% mechanic dimmer
- * Long Lifespan LEDs(more than 60,000 hours)