

Digital Multimeters
Model: 890G+ 890H+



Features

Model	890G+	890H+
TRUE RMS	√	√
NCV test	√	√
Live wire test	√	√
Input terminal LED Indication	√	√
High voltage LED Indication	√	√
Diode & Continuity test	√	√
Low battery indication	√	√
Backlight	√	√
Flash light	√	√
Auto power off	√	√
Data Hold	√	√
Max/Min. value	√	√
Max display	6000	6000
Operation method	Manual	Auto

Specifications

Model	Range	890G+	890H+
DC V	600mV/6V/60V/600V/1000V	±(0.5%+3)	±(0.5%+3)
AC V	6V/60V/600V/750V	±(0.8%+5)	---
	600mV/60V/600V/750V	---	±(0.8%+5)
DC A	60uA/60mA/600mA/10A	±(1.2%+3)	---
	600uA/6000uA/60mA/600mA/10A	---	±(1.2%+3)
AC A	60mA/600mA/10A	±(1.5%+3)	---
	600uA/6000uA/60mA/600mA/10A	---	±(1.5%+3)
Resistance	600Ω/6kΩ/60kΩ/600kΩ/6MΩ/60MΩ	±(1.0%+3)	±(1.0%+3)
Capacitance	10nF/100nF/1000nF/10uF/100uF/1000uF/10mF/100mF	±(3.5%+20)	±(3.5%+20)
Frequency	10Hz/100Hz/1000Hz/10kHz/100kHz/1000kHz/10MHz	±(1.0%+3)	±(1.0%+3)
Duty Cycle	1~99%	±(3.0%+3)	±(3.0%+3)
Temperature	(-20~1000)°C/(-4 ~ 1832)°F	---	±(1.0%+5)

General Information

Model	890G+	890H+
Power Supply	2 * 1.5V AAA Battery	
Product weight	320g	
Product size	186cmx88cmx54cm	
Product color	black + orange	
Standard accessories	Test leads, User manual, Temp. probe (only for 890H+)	