

Digital Multimeters
Model: 88B 88C 88E



Features

Model	88B	88C	88E
Diode & continuity buzzer	√	√	√
Peak value holding	---	√	---
Transistor Test	√	√	---
Max./Min Value	√	---	√
True RMS	√	√	√
Low battery indication	√	√	√
Data hold	√	√	√
Auto power off	√	√	√
Backlight	√	√	√
Live wire test	√	---	---
Duty cycle	---	---	√
Sampling rate	3 times/s	3 times/s	3 times/s
Operation way	Manual range	Manual range	Manual range
Max. Display	1999	1999	3999
LCD size	65×45mm	65×45mm	65×45mm

Specifications

Model	Range	88B	88C	88E
DC V	200mV/2V/20V/200V/1000V	$\pm(0.5\%+3)$	$\pm(0.5\%+3)$	---
	40mV/400mV/4V/40V/400V/1000V	---	---	$\pm(0.5\%+4)$
AC V	2V/20V/200V/750V	$\pm(0.8\%+5)$	---	---
	200mV/2V/20V/200V/750V	---	$\pm(0.8\%+5)$	---
	4V/40V/400V/750V	---	---	$\pm(0.8\%+6)$
DC A	200uA/2mA/20mA/200mA/20A	$\pm(1.2\%+8)$	---	---
	2mA/20mA/200mA /20A	---	$\pm(0.8\%+3)$	---
	400uA/4mA/40mA/400mA/20A	---	---	$\pm(1.0\%+10)$
AC A	20mA/200 mA/20A	$\pm(1.0\%+5)$	---	---
	2mA/20mA/200mA /20A	---	$\pm(1.0\%+5)$	---
	400uA/4mA/40mA/400mA/20A	---	---	$\pm(1.5\%+5)$
Resistance	200Ω/2kΩ/20kΩ/200kΩ/2MΩ/20MΩ/200MΩ	$\pm(0.8\%+3)$	---	---
	200Ω/2kΩ/20kΩ/200kΩ/2MΩ/20MΩ/2000MΩ	---	$\pm(0.8\%+3)$	---
	400Ω/4kΩ/40kΩ/400kΩ/4MΩ/40MΩ	---	---	$\pm(0.8\%+4)$
Capacitance	20nF/200nF/2uF/20uF/200uF/2000uF	$\pm(3.5\%+20)$	---	---
	20nF/200nF/2uF/20uF/200uF	---	$\pm(2.5\%+20)$	---
	40nF/400nF/4uF/40uF/200uF	---	---	$\pm(2.5\%+8)$
Frequency	10Hz/100Hz/1KHz/10KHz/100KHz/1MHz	$\pm(1.0\%+10)$	---	---
	2kHz/20kHz /200kHz/2000kHz/10MHz	---	$\pm(1.0\%+10)$	---
	100Hz/1000Hz/10KHz/100KHz/1MHz/10MHz	---	---	$\pm(0.5\%+4)$
Inductance	2mH/20mH/200mH/2H/20H	---	$\pm(2.5\%+20)$	---
Temperature	(-20 ~ 1000)°C /(0 ~ 1832)°F	$\pm(1.0\%+5)$	$\pm(1.0\%+5)$	$\pm(1.0\%+5)$

General Information

Model	88B	88C	88E
Power supply	6F22,9V*1		
Product color	Black+ Orange		
Product weight	400g		
Product size	189×97×35mm		
Standard accessories	Test leads, battery, manual, temperature probe		