

Digital Clamp Meters  
 Model: 606D 606E



**Features**

Models	606D	606E
Diode & Continuity Test	√	√
Data hold	√	√
NCV Measurement	√	√
True RMS	√	√
Low battery indication	√	√
Auto power off	√	√
Overload protection	√	√
Backlight	√	√
Torch light	√	√
DCA zeroing	---	√
Max Display	3999	3999
Sampling Rate	3times/second	
Jaw Size	32mm	32mm

**Specifications**

Function	Range	606D	606E
DC V	400mV/4V/40V/400V/600V	± (0.5%+5)	± (0.5%+5)
AC V	4V/40V/400V/600V	± (1.0%+5)	± (1.0%+5)
AC A	4A/40A/400A/600A	± (2.5%+5)	---
	40A/400A/600A	---	± (2.5%+5)
DC A	40A/400A/600A	---	± (2.5%+5)
Resistance	400Ω/4kΩ/40kΩ/400kΩ/4MΩ/40MΩ	± (1.0%+5)	± (1.0%+5)
Capacitance	10nF/100nF/1000nF/10uF/100uF/1000uF/10mF	± (4.0%+5)	± (4.0%+5)
Frequency	10Hz/100Hz/1000Hz/10kHz/100kHz/1000kHz/10MHz	± (1.0%+3)	± (1.0%+3)
Temperature	(-20~1000) °C / (-4~1832) °F	± (2.0%+3)	± (2.0%+3)
Duty cycle	1% -99%	± (3.0%+3)	± (3.0%+3)

**General Information**

Model	606D	606E
Power Supply	AAA,1.5Vx2	
Product color	Black+ Orange	
Product weight	300g	
Product size	175x66x30mm	
Standard accessories	Test leads, battery, manual, pouch, temperature probe	