

Digital Clamp Meters

Model: 6016B+ 6056D 3218+



Features

Model	6016B+	6056D	3218+
Diode & continuity test	√	√	√
True RMS	√	√	√
Low battery indication	√	√	√
Data Hold	√	√	√
Live wire detection	---	---	√
Max./Min. value	√	---	√
Sampling Rate	3 times/s	3 times/s	3 times/s
Operation Way	Manual range	Auto range	Auto range
Max. Display	1999	5999	1999
Clamp Size	30mm	30mm	30mm

Specifications

Function	Range	6016B+	6056D	3218+
DCV	200mV/2V/20V/200V/600V	± (0.5%+4)	---	± (0.5%+7)
	6V/60V/600V/1000V	---	± (0.5%+4)	---
ACV	2V/20V/200V/600V	± (0.8%+10)	---	± (0.8%+10)
	6V/60V/600V/750V	---	± (0.8%+10)	---
ACA	2A/20A/200A/600A	± (3%+5)	---	---
	400A/600A	---	± (3%+5)	---
DCA	200uA/2000uA/20mA/200mA/2A/20A/200A/600A	---	---	± (2%+3)
	400A/600A	---	± (3%+5)	---
Resistance	200Ω/2kΩ/20kΩ/200kΩ/2MΩ/20MΩ	± (0.8%+5)	---	± (1.0%+5)
	600Ω/6kΩ/60kΩ/600kΩ/6MΩ/60MΩ	---	± (0.8%+5)	---
Capacitance	600nF/6uF/60uF/600uF/6000uF	---	± (3%+5)	---
Frequency	100Hz/1kHz/10kHz/100kHz/1MHz/10MHz/60MHz	---	± (0.5%+3)	---
Temperature	-50°C~1000°C / -58°F~1832°F	---	± (1.0%+4)	---

General Information

Model	6016B+	6056D	3218+
Power Supply	AAA,1.5Vx2		
Product color	Black+ Orange		
Product weight	140g		
Product size	174mmx60mmx34mm		
Standard accessories	Test leads, batteries, manual, temperature probe (only for 6056D)		