

Digital Clamp Meters

Model: 606G 606H


Features

Model	606G	606H
Diode & continuity test	√	√
True RMS	√	√
NCV (non-contact voltage detection)	√	√
Flashlight	√	√
Data hold	√	√
Auto power off	√	√
LCD with backlight	√	√
Automatically recognize and measure based on the input voltage/current/resistance/current	---	√
Square wave output	√	---
Operation way	auto range	auto range
Max. display	5999	5999
Jaw open size	27mm	27mm

Specifications

Function	Range	606G	606H
DC V	6V/60V/600V/1000V	±0.5%+3	---
	6V/60V/600V/700V	---	±0.5%+3
AC V	6V/60V/600V/750V	±0.8+3	---
	6V/60V/500V	---	±0.8+3
AC A	6A/60A/600A	±2%+30	---
	60A/600A	---	±2%+30
Resistance	600Ω/6kΩ/60kΩ/600kΩ/6MΩ/40MΩ	±0.8%+3	---
	600Ω/6kΩ/60kΩ/600kΩ/6MΩ/60MΩ	---	±0.8%+3
Capacitance	60nF/600nF/6uF/60uF/600uF/6mF/30mF	±3.5%+20	---
	10nF/100nF/1uF/10uF/100uF/1mF/10mF/60mF	---	±3.5%+20
Frequency	10Hz/100Hz/1kHz/10kHz/100kHz/1MHz/10MHz	±0.1%+3	---
Temperature	-20°C~1000°C / 0°F ~ 1832°F	±1.0%+5	---

General Information

Model	606G	606H
Power Supply	AAA,1.5Vx2	
Product color	Black+ Orange	
Product weight	300g	
Product size	176x67x32mm	
Standard accessories	Test leads, batteries, manual, temperature probe (only for 606G)	