

Digital Insulation Resistance Testers

Model: 60B+ 60D+



Features

Model	60B+	60D+
Low Battery Indication	√	√
Backlight display	√	√
Alarm function	√	√
Over load indication	√	√
Unit symbol display	√	√
Auto power off	√	√
Max. display	1999	
LCD size	85x60mm	
Operation condition	(0~40)°C, 30%RH~85%RH	
Input Impedance	1MΩ	
Frequency Response	(50-200) Hz	
Over Range Display	"1"	

Specifications

Function	Range	60B+	60D+
Measuring voltage	250V/500V/1000V	±10%	---
	1000V/2500V	---	±20%
Resistance	250V 0.1MΩ—20MΩ 20MΩ—500MΩ	± (4%+2)	---
	500V 0.1MΩ—50MΩ 50MΩ—1000MΩ		
	1000V 0.1MΩ—100MΩ 100MΩ—2000MΩ		
	1000V 6.0MΩ-199.9MΩ 0.06GΩ-1.999GΩ		
Resistance	2500V 0.6GΩ-19.99GΩ 5MΩ-199.9MΩ 0.05GΩ-1.999GΩ	---	± (5%+5)
Current of short circuit	---	1.8mA	<4mA
AC V	750V	± (1%+6)	± (1%+6)

General Information

Model	60B+	60D+
Power Supply	6x1.5V AA batteries AC adapter (not included)	8x1.5V AA Batteries AC adapter (not included)
Product color	Black + orange	
Product weight	175×110×70mm	
Product size	630g	
Standard accessories	Test leads, batteries, manual, shoulder strap	