

## **Weather Stations**

Weather Station (None-WIFI )

Model: 0345-026T



#### **Features**

| Model 0345-026T                            |   |                                       |   |                                    |
|--|---|---------------------------------------|---|------------------------------------|
| Temperature (indoor +outdoor)              | • | Rainfall data                         | • | Snooze                             |
| Humidity (indoor +outdoor)                 | • | UV index                              | Χ | Backlight                          |
| Dew point (indoor +outdoor)                | • | Light meter                           | Χ | Beeper on/off ●                    |
| PM2.5 PM1.0 (indoor)                       | Χ | Solar radiation                       | Χ | Max./Min value                     |
| Carbon Dioxide CO2 (indoor)                | Χ | Time and calendar                     | • | Low power indication               |
| Wind chill                                 | • | USB connection                        | • | Alarm                              |
| Wind speed                                 | • | WIFI connection                       | Χ | Wall hanging                       |
| Wind gust                                  | • | LORA connection                       | Χ | Soar powered •                     |
| Wind average                               | • | With data storage                     | Χ | Calibratable                       |
| Wind direction                             | • | View data on APP                      | Χ | °C and °F                          |
| Add additional 8 hygro-thermometer sensors | Χ | Support Weathercloud and Wunderground | Χ | m/s, km/h, mph, knots, ft/s or bft |
| Barometric (REL and ABS) pressure          | • | Weather forecast (24H-48H)            | • | mmhg, inHg, hPa                    |
| Moon phase                                 | • | View data on a software               | • | W/m², fc or lux. X                 |



# **Weather Stations**

### **Specifications**

| Measurement             | Range  | Accuracy                               | Resolution                       |  |  |
|-------------------------|--|--|----------------------------------|--|--|
| Indoor Temperature      | 0 to 60 °C   | ± 1 °C                                 | 0.1 °C                           |  |  |
| Outdoor Temperature     | -40 to 60 °C   | ± 1 °C                                 | 0.1 °C                           |  |  |
| Indoor Humidity         | 10 to 99 %   | ± 5% (20% - 90%)                       | 1 %                              |  |  |
| Outdoor Humidity        | 10 to 99%  | ± 5% (20% - 90%)                       | 1 %                              |  |  |
| Rainfall                | 0 to 9999mm  | <15mm: ±1 mm,<br>15mm to 9999mm: ±7%   | <1000mm (0.3mm)<br>>1000mm (1mm) |  |  |
| Wind Direction          | 0 - 360 °  | ± 10° (16 points compass)              | ± 1º (16 points compass)         |  |  |
| Wind Speed              | 0 to 50 m/s  | 2m/s~10m/s: ±3m/s<br>10m/s~50m/s: ±10% | 0.1 m/s                          |  |  |
| Barometric Pressure     | 300 -1100 hpa  | ± 3 hpa                                | 0.1 hpa                          |  |  |
| Transmission interval   | 16s  |  |                                  |  |  |
| Transmission distance   | 100m in open area  |  |                                  |  |  |
| Transmission frequency  | 433MHz   |  |                                  |  |  |
| Max. transmission power | 0.5mW  |  |                                  |  |  |
| Interface               | USB  |  |                                  |  |  |
| Data storage            | 5000 groups (about 3 days data, when the data update rate is 1 minute) |  |                                  |  |  |

### **General Information**

| Model                | 0345-026T   |
|----------------------|---|
| Power supply         | Receiver: 3 x AAA batteries  Transmitter: 3 x AA batteries  Power adaptor: 5V/1A or 5.9V/0.5A   |
| Product size         | Receiver:142x120x22mm (LCD: 112x94mm) Transmitter:380x180x280mm   |
| Product weight       | Receiver:250g<br>Transmitter: 1000g   |
| Standard accessories | Receiver x 1 / Transmitterx1/ metal gasket x 4 / U-bolt nuts x4/ U-bolt(M5) x2 / stainless steel base x 1/ wrench (M5) x1 / screwdriver (M3) x 1 / Rubber plug x 2 / manual x 1/ power adaptor x1 / USB cable x 1 / software CD |