

Multi-function Process Calibrators

Signal Generators

Model: 71A 71B 71C



Features

Model	71A	71B	71C
Manual step output	√	√	√
Auto waveform output	√	√	√
Flash light	√	√	√
LCD display with backlight	√	√	√
Auto power-off	√	√	√
Low battery indication	√	√	√

General Information

Model	71A 71B 71C
Power supply	3×1.5V AAA
Product color	Black + orange
Product size	151mm×75mm×42 mm
Product weight	500g
Standard accessories	Manual, test leads, alligator clips, fuse, pouch

Specifications

Source function	Range	Best accuracy		
Model		71A	71B	71C
DC mV	110mV	0.2%+4	0.2%+4	0.2%+4
DC V	10V	0.2%+4	0.2%+4	0.2%+4
DC mA	0 ~ 22mA	0.2%+4	0.2%+4	0.2%+4
Sink current	0 ~ 22mA	0.2%+4	0.2%+4	0.2%+4
Thermocouple	8 types (R/S/K/E/J/T/B/N)	---	0.2%+4	---
Measurement function				
DC mV	-10 ~ 110mV	0.2%+4	0.2%+4	---
DC V	-5 ~ 30V	0.2%+4	0.2%+4	---
DC mA	0 ~ 22mA	0.2%+4	0.2%+4	---
Loop power supply	24V	10%	10%	---
Thermocouple	8 types (R/S/K/E/J/T/B/N)	---	0.2%+4	---
Switch	Close/ open	√	√	---