

R24100

Residential Energy Storage Battery Series



[R24100]

Widely Compatibility: support conventional VRLA powered system.

Superior Safety: build-in BMS——eliminates the risk of explosion or combustion due to high impact, overcharging or short circuit situation with safe lithium iron phosphate chemist.

Flexible Configuration: racked design easy to be installed. Optional HMI, max. 2 sets in parallel supported.

High Performance: support 1C or 100A charge/discharge, widely working temperature. Cells comply with CE, UL and IEC standards.

Technical Parameters

Nominal Voltage (V)	25.6
Nominal Capacity (Ah)	100
Total Energy (Wh)	2560
Operating Voltage Range (V)	18.4 ~ 29.2
Standard Charge/Discharge Current (A)	50 CH / 50 DCH
Max. Charge/Discharge Current (A)	100 CH / 100 DCH
Peak Output Current (A)	150@10s
Lithium Chemistry	LiFePO ₄
Cycle Life	6000 @ 0.5C 80% DOD
Design Life	20 years
Scalability	Max 2S or 2P
Installation	Rack type

Mechanical Specifications


Dimension (mm)	W442 * D400 * H133
Weight (kg)	Approx. 24
Communication	/
Ingress Rating	IP 54
Safety Standards	UN38.3, CE

Environmental Specifications


Storage Temperature (°C)	-20 ~ 55
Operating Temperature Charge (°C)	0 ~ 55
Operating Temperature Discharge (°C)	-20 ~ 60
Operating Relative Humidity	5 ~ 95%

Operating Performance

Different Temperature Self Discharge Curve



Different DOD Discharge Cycle Life Curve (0.5C)



Notes:

Battery should be kept in a dry and ventilated place, avoid direct contact with corrosive substances, also away from sources of fire and heat. Keep the SOC of the battery above 50% if you need to store it for an extended long period. It should be refresh charged every 3 months regularly and SOC should be maintained at about 50% if battery will be stored for a long term.

