

8GE+2SFP Ports Full Gigabit Managed PoE Switch

Model: PS2802SFG



Product Introduction

The PS2802SFG is a full gigabit L2+ managed POE fiber switch. It has 8*10/100/1000Base-T POE ports and 2*100/1000Base-X SFP fiber slot ports. Single port PoE power reaches 30W. As a PoE power supply device, it can automatically detect and recognize the power receiving equipment that meets the standard and supply power through the network cable. It can supply power to POE terminal equipment such as wireless AP, webcam, VoIP phone, building visual access control intercom through network cable, to meet the network environment that needs high-density PoE power supply, suitable for hotels, campuses, parks, supermarkets, scenic spots, Factory quarters and SMB small and medium-sized enterprises form a cost-effective network.

The PS2802SFG has the L2+ full network management, support IPV4/IPV6 management, static route full line rate forwarding, security protection mechanism, complete ACL/QoS policy and rich VLAN functions, and is easy to manage and maintain. Supports multiple network redundancy protocols STP/RSTP/MSTP (<50ms) and (ITU-T G.8032) ERPS to improve link backup and network reliability. When one-way network fails, communication can be quickly restored to ensure important Uninterrupted communication for applications. According to the actual application requirements, you can configure multiple application services such as PoE power management, port traffic control, VLAN division, and SNMP through the Web network management mode.

Features

- ◎ 8GE+2SFP Full Giga 802.3af/at L2 Managed PoE Switch with 8Port PoE
- ◎ Supports PoE power up to 30W for each port
- ◎ Supports PoE IEEE 802.3af/at compliant PDs
- ◎ Internal power adapter supply 120W
- ◎ WEB/CLI managed modes, SNMP, RMON bring abundant management features
- ◎ Support QVLAN, QoS and IGMP snooping optimize voice and video application
- ◎ Support QOS, STP/RSTP, IGMP, DHCP, SNMP, WEB, VLAN, ERPS etc.

Integrated Solution, Better Living

Specification

Model	PS2802SFG
Interfaces	
Fixed Port	8*10/100/1000Base-T PoE ports (Data/Power)
	2*100/1000Base-X uplink SFP slot ports (Data)
	1 * RS232 console port (115200, N,8,1)
Ethernet Port	10/100/1000Base-T(X), Auto-sensing,Full/half duplex MDI/MDI-X self-adaption
Twisted Pair Transmission	10BASE-T: Cat3,4,5 UTP (≤100 meter)
	100BASE-TX: Cat5 or later UTP (≤100 meter)
	1000BASE-T: Cat5e or later UTP (≤100 meter)
SFP Slot Port	Gigabit SFP optical fiber interface, default matching optical modules (optional order single-mode / multi-mode, single fiber / dual fiber optical module. LC)
Optical Cable	Multi-mode: 850nm 0 ~ 550M, single mode: 1310nm 0 ~ 40KM, 1550nm 0 ~ 120KM.
Network Management Type	L2+
Network Protocol	IEEE802.3 10BASE-T; IEEE802.3i 10Base-T;
	IEEE802.3u 100Base-TX;
	IEEE802.3ab 1000Base-T
	IEEE802.3z 1000Base-X
	IEEE802.3x
Forwarding Mode	Store and Forward (Full Wire Speed)
Switch Property	
Switching Capacity	20Gbps
Forwarding, Rate@64byte	14.88Mpps
MAC	8K
Buffer Memory	4.1M
Jumbo Frame	10K
Physical Characteristics	
LED Indicator	Power:PWR(yellow), system :SYS(green), network ;Link/Act(yellow), POE: PoE (green), ,Fiber port: L/A(green)
Reset Switch	Yes, One-button factory reset
PoE Port	Port 1 to 8 IEEE802.3af/at @ POE
PoE Management	Total power limit of PoE power supply
	PoE output power allocation, off& af &at
	PoE output priority configuration
	PoE working status
	Delay start of power supply
	Scheduling of PoE operation and time
Power Supply Pin	Default 1/2 (+), 3/6 (-)
Max Power Per Port	30W; IEEE802.3af/at

Total PWR / Input Voltage	120W/250W (AC100~240V)
Power Consumption	Standby:<4W; Full load:<120W
Power Supply	Built-in power supply, AC 100~240V 50~60Hz 2.3A
Operation TEMP / Humidity	-20~+55°C;5%~90% RH Non condensing
Storage TEMP / Humidity	-40~+75°C;5%~95% RH Non condensing
Dimension (L*W*H)	207*140*44mm
Net /Gross Weight	<1.7kg / <2.2kg
Installation	Desktop, 19-inch 1U cabinet
Lightning protection / protection level	Lightning protection: 4KV 8/20us; Protection level: IP30
Certification	CCC; CE mark, commercial; CE/LVD EN60950; FCC Part 15 Class B; RoHS;
Warranty	3 years, lifelong maintenance.
Interface	IEEE802.3X (Full-duplex)
	Broadcast storm control based on port speed
	The speed limit of the message flow in the access port. The minimum particle size is 64Kbps.
	Port temperature protection setting
Layer 3 Features	Port green Ethernet Energy-saving setting
	L2+ Network management
	IPV4/IPV6 management
	L3 soft routing forwarding, Static route, Default route @ 128 pcs, APR @ 1024 pcs
VLAN	4K VLAN based on port, IEEE802.1q
	VLAN based on the protocol
	VLAN based on MAC
	Voice VLAN, QinQ configuration
	Port configuration of Access, Trunk, Hybrid
Port Aggregation	LACP, Static aggregation
	Max 5 aggregation groups and 8 ports per group.
Spanning Tree	STP (IEEE802.1d), RSTP (IEEE802.1w), MSTP (IEEE802.1s)
Industrial Ring Network Protocol	G.8032 (ERPS), Recovery time less than 20ms
	255 Ring at most, Max 1024 devices per ring.
Multicast	IGMP Snooping v1/v2, Max 1024 multicast groups, Fast log out
	MLD Snooping v1/v2, Multicast VLAN
Port Mirroring	Bidirectional data mirroring based on port
QoS	Diff-Serv QoS, Priority Mark/Remark
	8*Output queues of each port
	802.1p/DSCP priority mapping

	Queue Scheduling Algorithm (SP, WRR, SP+WRR)
	Flow-based Packet Filtering
	Flow-based Redirection
	Flow-based Rate Limiting
ACL	L2 to L4 packet filtering, matching first 80 bytes message. Provide ACL based on MAC, Destination MAC address, IP Source, Destination IP, IP Protocol Type, TCP/UDP Port, TCP/UDP Port Range, and VLAN, etc. Port-based Issuing ACL.
	ACL based on port and VLAN
Security	User hierarchical management and password protection
	SSH 2.0, SSL, Port isolation, ARP message speed limit
	Broadcast storm control, Backup for host datum
	IEEE802.1X & MAC address authentication
	Mac black holes, IP source protection
	AAA & RADIUS, MAC learning limit
	ARP inspection, Anti-DoS attack
	IP-MAC-VLAN-Port binding
DHCP	DHCP Client, DHCP Snooping, DHCP Server, DHCP Relay
Management	Console/AUX Modem/Telnet/SSH2.0 CLI
	Web Management (HTTPS)
	Download & Management on FTP, TFTP, Xmodem, SFTP, SNMP V1/V2C/V3
	One-key recovery
	NTP, System work log, Ping Test
	Cable Diagnose, LLDP
	CPU instant utilization status view
	NMS - Smart Network Management System Platform (LLDP+SNMP)
System	Web browser: Mozilla Firefox 2.5 or higher, Google browser chrome V42 or higher, Microsoft Internet Explorer 10 or later;
	Category 5 Ethernet network cable
	TCP/IP, network adapter, and network operating system (such as Microsoft Windows, Linux, or Mac OS X) installed on each computer in a network
Certification	
Certification	CE, FCC, RoHS,
Package Contents	
Switch	1pcs
Power cord	1pcs
Quick installation guide	1pcs

HIMAX



HIMAX TECHNOLOGY LIMITED

www.himax-technology.com

Email: sales@himax-technology.com

F10, Fuhong Building, No.120 Yongfu Road, Qiaotou Community Fuhai Street, BaoanDistrict, Shenzhen China



Company Website